

---

## OT 60/220...240/12 P

CV Power supplies 12 V



---

### Areas of application

- Suitable for indoor and outdoor installations
- Ideal for mounting in very tight spaces

---

### Product benefits

- Versatile scope of application due to output power range of up to 120 W
- Very high efficiency and reliability
- High IP protection (up to IP67)
- High surge protection: up to 3 kV (L-N) / 6 kV (L/N-PE)

Technical data

Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Input voltage AC	198...264 V <sup>1)</sup>
Power factor $\lambda$	0.98/0.93 <sup>2)</sup>
ECG efficiency	86 % <sup>3)</sup>
Device power loss	9.0 W
Protective conductor current	<2.0 mA
Inrush current	35 A <sup>4)</sup>
Max. ECG no. on circuit breaker 10 A (B)	11
Max. ECG no. on circuit breaker 16 A (B)	17
Max. ECG no. on circuit breaker 25 A (B)	-
Surge capability (L-N)	3 kV
Nominal output voltage	12.5 V <sup>5)</sup>
Nominal output power	60 W <sup>6)</sup>
Galvanic isolation	SELV equivalent
Galvanic isolation primary/secondary	3.75 kV <sup>7)</sup>

<sup>1)</sup>  $V_{AC}$  / Permitted voltage range

<sup>2)</sup> Full load at 230 V/Half load at 230 V

<sup>3)</sup> At full load and 230 V

<sup>4)</sup>  $t_{width} = 170 \mu s$  (measured at 50 %  $I_{peak}$ )

<sup>5)</sup>  $\pm 0.5 V$

<sup>6)</sup> Partial load 0...60 W

<sup>7)</sup> SELV-equivalent

Dimensions & weight



Length	180.0 mm
Width	50.0 mm

## Product datasheet

Height	34.0 mm
Mounting hole spacing, length	171.0 mm
Product weight	700.00 g
Cable cross-section, input side	1.0 mm <sup>2</sup> <sup>1)</sup>
Cable cross-section, output side	1.0 mm <sup>2</sup> <sup>1)</sup>
Wire preparation length, input side	10 mm
Wire preparation length, output side	10 mm
Cable/wire length, input side	500 mm
Cable/wire length, output side	500 mm
Mounting hole spacing, width	14.0 mm <sup>2)</sup>

<sup>1)</sup> Flexible

<sup>2)</sup> Side mounting

### Colors & materials

Casing material	Metal
-----------------	-------

### Temperatures & operating conditions

Ambient temperature range	-25...+55 °C
Maximum temperature at tc test point	80 °C
Max.housing temperature in case of fault	100 °C
Permitted rel. humidity during operation	5...85 %

### Lifespan

ECG lifetime	50000 h <sup>1)</sup>
--------------	-----------------------

<sup>1)</sup> At tcase = 70°C at tc point / 10 % failure rate

### Additional product data

Encapsulated	No
--------------	----

### Capabilities

Dimmable	Yes <sup>1)</sup>
Dimming interface	Not dimmable
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
Short-circuit protection	Automatic reversible
No-load proof	Yes
Max. cable length to lamp/LED module	10 m
Suitable for fixtures with prot. class	II

<sup>1)</sup> With OPTOTRONIC dimmers

## Product datasheet




### Certificates & standards

Approval marks – approval	CE / ENEC 18 / CB / C-Tick
Standards	Acc. to IEC 61347-1/Acc. to IEC 61347-2-13/Acc. to IEC 62384/Acc. to CISPR 15/Acc. to IEC 61000-3-2/Acc. to IEC 61000-3-3/Acc. to IEC 61547
Protection class	II
Type of protection	IP67

### Logistical data

Temperature range at storage	-40...85 °C
------------------------------	-------------

### Download Data

File
 Product Datasheet OPTOTRONIC OT 60220-24012 P
 Declarations of conformity EC Declaration OT60120 220 240 12P
 Installation guide Instruction Sheet_OT 60220-24012 P

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321790811	OT 60/220...240/12 P	Shipping carton box 10	574 mm x 137 mm x 323 mm	25.40 dm <sup>3</sup>	7593.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.